



# Dresser Series 3 Meter with Electronic Transmitter (ICEX)

## Application and Operation

The Dresser Natural Gas Solutions (NGS) Meter with Electronic Transmitter (ICEX), is a single-channel, transistor output device that provides a non-compensated, high-frequency pulse output (four pulses per impeller shaft revolution) for applications requiring gas flow rate and totalization information.

A two-wire output from the ICEX is used to provide uncorrected flow rate or totalization data to accessory instruments or other totalizer devices. Loop power for the ICEX is supplied by the totalizer instrument. An optional cable for connecting to the MSC circular connector is available.

## Ordering Information

When ordering a Series B3 CTR (counter) meter, a 'transmitter ready' option can be specified for future installation of the Electronic Transmitter (conversion kit #399<sup>1</sup>). Existing Series B2 meters can be easily converted to the ICEX option using a complete accessory unit, Assembly #400, which includes a non-compensated counter and the transmitter for a specific meter size.

### With Meter Specify:

Meter model with ICEX (Example: 3M175 ICEX)

### As Complete Accessory Unit Specify:

Repair Assembly #400 Counter w/Electronic Xmtr (ICEX) and meter model

### As Conversion Kit<sup>1</sup> Specify:

Repair Assembly #399 CTR to ICEX and meter model

<sup>1</sup>Conversion Kit #399 may be used only on Series 3 Counters. Series B2 (TQM) Meters require a complete Accessory Unit Assembly #400.

## Features

- Provides a non-compensated, high-frequency pulse output
- Mounts on all Series B meter bodies
- Available factory installed or as a field installable conversion kit
- Enhances reliability by using Solid State components to eliminate mechanical switches
- Helps minimize maintenance
- Available in three connections styles: MS-style circular connector; 1/2-inch liquid tight type conduit fitting; or cable gland with 4-ft. cable.

## Specifications

<b>Applicable Sizes</b>	Series B Dresser meters 8C through 56M
<b>Loop Voltage</b>	3 - 30 VDC (Typ.)
<b>Supply Current</b>	10 mA (max.)
<b>Pulse Width</b>	2 milli-seconds (Typ.)
<b>Duty Cycle</b>	Flow rate dependent
<b>Rise/Fall Time</b>	20 $\mu$ s (Typ.)
<b>Connection Styles</b>	Circular connector, 1/2-inch liquid tight type conduit fitting, or cable gland with 4-ft. cable



Circular Connector



Conduit



Cable Gland

## Reference Data

Meter Type	Frequency	Volume Per Pulse		Pulses Per Volume		Flow Rate	Dimensional Drawings with ICEX	
	(Hz)	(CF)	(m <sup>3</sup> )	(CF)	(m <sup>3</sup> )	(ACFH)		
<b>8C175</b>	120.00	0.00185185	0.0000524386	540	19070	800	B3 8/11/15C	D056899-000
<b>11C175</b>	146.67	0.00208333	0.0000589934	480	16951	1,100	B3 2/3/5M	D056900-000
<b>15C175</b>	166.67	0.00250000	0.0000707921	400	14126	1,500	B3 23/38/56M	D057701-000
<b>2M175</b>	111.11	0.00500000	0.0001415843	200	7063	2,000	1M/3M 300	D058612-000
<b>3M175</b>	133.33	0.00625000	0.0001769803	160	5650	3,000	1M/3M 740/1480	D057373-000
<b>5M175</b>	150.00	0.00925926	0.0002621931	108	3814	5,000	23M232 4"	D057745-000
<b>7M175</b>	124.45	0.01562500	0.0004424508	64	2260	7,000	2M NPLD	D059081-000
<b>11M175</b>	122.22	0.02500000	0.0007079213	40	1413	11,000	5M/7M 1480	D057442-000
<b>16M175</b>	120.00	0.03703704	0.0010487722	27	953	16,000	8/11/15C NPLD	D057415-000
<b>23M232</b>	127.78	0.05000000	0.0014158425	20	706	23,000	11M 1480	DO59535-000
<b>23M175</b>	69.00	0.09259259	0.0026219306	11	381	23,000		
<b>38M175</b>	76.00	0.13888889	0.0039328958	7	254	38,000		
<b>56M175</b>	89.60	0.17361111	0.0049161198	6	203	56,000		
<b>1M300</b>	55.55	0.00500000	0.0001415843	200	7063	1,000		
<b>3M300</b>	133.33	0.00625000	0.0001769803	160	5650	3,000		
<b>1M740</b>	75.00	0.00370370	0.0001048772	270	9535	1,000		
<b>1M1480</b>	75.00	0.00370370	0.0001048772	270	9535	1,000		
<b>3M740</b>	166.67	0.00500000	0.0001415843	200	7063	3,000		
<b>3M1480</b>	166.67	0.00500000	0.0001415843	200	7063	3,000		
<b>5M1480</b>	100.00	0.01388889	0.0003932896	72	2543	5,000		
<b>7M1480</b>	124.45	0.01562500	0.0004424508	64	2260	7,000		
<b>11M1480</b>	97.78	0.03125	0.000884902	32	1130	11,000		

### The following ratings apply to the ICEX:

- Electrical Rating: 3-28Vdc, 0-10mA
- Class I, Zone 0, AEx ia IIC T4 Ga
- Class I, Zone 0, Ex ia IIC T4 Ga

### Dresser Meters & Instruments

16240 Port Northwest Drive

Houston, TX 77041

T: 1-800-521-1114

F: 1-800-335-5224

The Dresser Logo and all Trademarks containing the term "Dresser" are the property of Dresser, LLC, a subsidiary of Baker Hughes, a GE Company.



[www.dresserngs.com](http://www.dresserngs.com)

Dresser ICEX Meter Fact Sheet NGS.MI.0045

11.18